07448

OP 0 13+027

DESIGN.

ΕX

J. A. DEKNATEL.

BUTTON.

No. 13,027.

Patented July 11, 1882.



WITNESSES:

le Bedgwick

INVENTOR:

Y Mum

ATTORNEYS.

United States Patent Office.

JOHN A. DEKNATEL, OF BROOKLYN, NEW YORK.

DESIGN FOR A BUTTON.

SPECIFICATION forming part of Design No. 13,027, dated July 11, 1882.

Application filed May 22, 1882. Term of patent 7 years.

To all whom it may concern:

Be it known that I, JOHN A. DEKNATEL, of Brooklyn, in the county of Kings and State of New York, have invented and produced a new 5 and original Design for Buttons, of which the following is a full, clear, and exact description.

Reference is to be had to the accompanying drawing, forming part of this specification, in which my newly-designed button is shown.

The leading feature of my new design consists in a transverse bar, from each side of which two bows, curved toward each other, project, which bows surround two opposite beaded volutes on each side of the bar. The ends of the transverse bar are widened and ornamented in some manner, and the outer ends of the bows, at the sides of the bar, are also widened and ornamented. An arrow projects from each side of the bar in such a manner that the arrow-point will be between the ends of the bows, and the feather end of the arrow rests against the bar. A single bead is provided above one end of the bar, and two sector-shaped or triangular fields are arranged at the sides of this bead. The sides of the bar, the bows, the arrows, beads, and fields are beveled.

This design can also be used for breastpins, 30 medallions, and other like disk ornaments.

Having thus fully described my invention, I claim as new and desire to secure by Letters Patent—

1. The herein-described design for buttons, consisting of a transverse bar and of bows projecting from the sides of the bar and volutes contained within these bows, as set forth.

2. The herein-described design for buttons, consisting of a transverse bar, of bows projecting from the sides of this bar, and of arrows projecting from the sides of the bar between the free ends of the bows, as set forth.

3. The herein-described design for buttons, consisting of a transverse bar having the ends widened and of bows projecting from the sides 45 of the bar and having the ends widened, as set forth.

4. The herein-described design for buttons, consisting of a transverse bar, bows projecting from the sides of the bar, a bead at one 50 end of the bar, and two triangular or sector-shaped fields at the sides of this bead, as set forth.

JOHN A. DEKNATEL.

Witnesses:
OSCAR F. GUNZ,
C. SEDGWICK.